







## AZ3 HTE 2 Pistola Manual de Gravidade

# HTE 2


HIGH TRANSFER  
EFFICIENCY

- Acabamento polido  
Superfície lisa e polida de fácil limpeza
- Design ergonômico  
Gatilho e cabo novos para aliviar o estresse na pintura
- Peso leve & corpo bem balanceado  
Cabeçote de 20-50g mais leve que os modelos anteriores
- Nova válvula de ar  
Aumento na precisão do controle de fluxo de ar
- Caneca em AKULON melhorado  
Construída utilizando técnica de trança de fios
- Spare parts compatible with previous AZ3 HTE



MODELO	 Ø mm	 No.	 bar	 ml/min	 l/min	 mm
AZ3 HTE2	1.3	10-15HTE	2.0	140	200	240
	1.5			160		260
	1.8	18-20HTE		250	215	300

Air Nipple: G1/4" - Fluid Nipple: G1/4"

Model	AZ3 HTE 2	
Test	Transfer Efficiency according to EN 13966-1	
Authority	IPA Fraunhofer Institut	
Date	27/03/2008	
Transfer efficiencies achieved with the materials detailed in the test report were:		
2K Primer Coat	89 %	
Water based Base Coat	79 %	
2K Clear Coat	84 %	
 <small>Certification available on <a href="http://www.airgunsa.com">www.airgunsa.com</a></small>		

CE  II 2 GX

declaration of A TEX conformity for use in zone 1 and in zone 2